

V800 UPS



Front View



Back View

V1200 UPS



Front View



Back View



Overload and Overcharge Protection



Universal Output Sockets



Built-in AVR Function



220-240VAC

MODEL	V800		V1200	
Capacity (VA/Watts)	800VA		1200VA	
INPUT				
Voltage	220-240VAC			
Frequency	50/60Hz (±10%)			
OUTPUT				
Voltage (On Battery)	Simulated sine wave at nominal voltage ±10%			
Frequency (On Battery)	50/60Hz ±1Hz			
Transfer time	Typical 2-6 ms, 10ms max.			
Voltage Regulation (AVR)	Automatically increase/decrease output voltage by -13% to +10% if the nominal input voltage fluctuates from -26% to +22%			
BATTERY				
Battery type & Number	12V/7AH x 1	12V/7AH x 1	12V/7AH x 2	12V/7AH x 2
Typical recharge time	6-8 hours recover to 90% capacity			
SYSTEM FEATURES				
Protection	Overload and overcharge protection			
ALARM INDICATOR				
In Battery Mode	Beeping every 10 seconds			
Low battery	Beeping every 1 second			
Overload	Beeping every 0.5 second			
Faulty	Continuously beeping sound			

MCL Bhd (275417-H)

Nationwide Service Centre:

Kuala Lumpur Tel: 03-80249909

Johor Bahru Tel: 07-3522 533

Penang Tel: 04-2266 366

Kuantan Tel: 016-9220 611/
016-9220 609

Melaka

Kota Kinabalu

Kuching

Miri

Tel: 06-2825 389

Tel: 088-318 120

Tel: 082-360 476

Tel: 085-660 499

Authorised Reseller: