



Built-in AVR
Function



220~240VAC



4x Universal
Output Sockets



Overload & Overcharge
Protection



● **UPS V2000**

MODEL	V2000
Capacity (VA)	2000VA
Phase	Single phase
INPUT	
Voltage	220~240VAC
Frequency	50/60Hz (±10%)
Power Factor	0.6
OUTPUT	
Voltage (On Battery)	Simulated sine wave at nominal voltage ±10%
Frequency (On Battery)	50/60Hz ±1Hz
Transfer Time	Typical 2-6 ms, 10ms max.
Voltage Regulation (AVR)	Automatically increase/decrease output voltage by -13% to +10% if the nominal input voltage fluctuates from -26% to +22%
BATTERY	
Battery type & Number	12V/9AH x 2
Typical Recharge time	6-8 hours recover to 90% capacity
SYSTEM FEATURES	
Protection	Overload and overcharge protection
ALARM INDICATOR	
In Battery Mode	Beeping every 10 seconds
Low Battery	Beeping every 1 second
Overload	Beeping every 0.5 second
Faulty	Continuously beeping sound
LCD Display (LCD Version)	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault and Battery Low

PHYSICAL	
Approx. net weight (kg)	Approx. 10.5
Approx. Dimension D*W*H (mm)	380* 158* 198
MANAGEMENT	
Communication Port	USB