



Built-in AVR  
Function



220~240VAC



Universal Output  
Sockets



Overload & Overcharge  
Protection



## V800-L

MODEL	V800-L
Capacity (VA)	800VA
Phase	Single phase
<b>INPUT</b>	
Voltage	220~240VAC
Frequency	50/60Hz (±10%)
Power Factor	0.6
<b>OUTPUT</b>	
Voltage (On Battery)	Simulated sine wave at nominal voltage ±10%
Frequency (On Battery)	50/60Hz ±1Hz
Transfer Time	Typical 2-6 ms, 10ms max.
Voltage Regulation (AVR)	Automatically increase/decrease output voltage by -13% to +10% if the nominal input voltage fluctuates from -26% to +22%
<b>BATTERY</b>	
Battery type & Number	12V/7Ah x 1
Typical Recharge time	6-8 hours recover to 90% capacity
<b>SYSTEM FEATURES</b>	
Protection	Overload and overcharge protection
<b>ALARM INDICATOR</b>	
In Battery Mode	Beeping every 10 seconds
Low Battery	Beeping every 1 second
Overload	Beeping every 0.5 second
Faulty	Continuously beeping sound
<b>PHYSICAL</b>	
Approx. net weight (kg)	Approx. 4.3
Approx. Dimension D*W*H (mm)	298* 101* 142